



PRODUCT DESCRIPTION

Provides smoke control and limited fire protection when installed in approved assemblies. C.S.F.M. (California State Fire Marshall) or W.H.I. label (Warnock-Hersey, Inc.).

All doors meet or exceed current industry standards.

- Current WDMA I.S. 1A
- W.I.C. Section 20
- A.W.I. Section 1300 when specified

ITEM SPECIFICATIONS

| | |
|------------------------------------|---|
| Maximum Size | 4'-0" x 10'-0" |
| Thickness | 1 ³ / ₄ " only |
| Stiles | 1 ¹ / ₄ " laminated hardwood bonded to core. Softwood available. |
| Rails/Lock Blocks | 1 ¹ / ₄ " minimum softwood, larger rails avail. |
| Core | Particle board or staved lumber core |
| Adhesives | Type 2. Type 1 available. |
| Faces | All commercially available hardwood species, medium density overlay, and high -pressure plastic laminates |
| Vision Panels & Louvers | See C.S.F.M. or W.H.I. specifications |
| Prefitting | May be prefit to net sizes as specified |
| Machining | May be factory machined for hardware as specified |
| Warranty | Up to life of the original installation. See full Haley Brothers Warranty for specific coverages |
| Short Form Specification | Doors shall be "20 Minute Label," manufactured according to the specifications shown in the Haley catalog |

NOTE: All dimensions are before trimming.