


H **PRODUCT DESCRIPTION**

Provides smoke control and limited fire protection when installed in approved assemblies. C.S.F.M. (California State Fire Marshall) or W.H.I. label (Warnock-Hersey, Inc.).

All doors meet or exceed current industry standards.

- Current WDMA I.S. 1A
- W.I.C. Section 20
- A.W.I. Section 1300 when specified

H **ITEM SPECIFICATIONS**

Maximum Size	4'-0" x 8'-0" Singles Only
Thickness	1 ³ / ₄ " only
Stiles	Hinge and latch stile. 1" firestop with hardwood edgeband.
Rails/Lock Blocks	1 ¹ / ₂ " minimum firestop, larger rails avail.
Core	Particle board or staved lumber core
Adhesives	Type 2. Type 1 available.
Faces	All commercially available hardwood species, medium density overlay, and high -pressure plastic laminates
Vision Panels & Louvers	See C.S.F.M. or W.H.I. specifications
Prefitting	May be prefit to net sizes as specified
Machining	May be factory machined for hardware as specified
Warranty	Up to life of the original installation. See full Haley Brothers Warranty for specific coverages
Short Form Specification	Doors shall be "20 Minute Label," manufactured according to the specifications shown in the Haley catalog

NOTE: All dimensions are before trimming. "Firestop" is a product of Georgia-Pacific Corporation.