



PRODUCT DESCRIPTION

Mineral core fire doors intended for use where 45, 60 min. fire barriers are required. W.H.I. label (*Warnock-Hersey, Inc.*).

All doors meet or exceed current industry standards.

- Current WDMA I.S. 1A
- W.I.C. Section 20
- A.W.I. Section 1300 when specified

ITEM SPECIFICATIONS

Maximum Size	3'-0" x 10'-0" single swing 4'-0" x 9'-0" single swing 8'-0" x 8'-0" double egress pairs
Thickness	1 ³ / ₄ " only
Stiles	Latch stile ³ / ₄ " "Firestop" Hinge stile 1" "Firestop" Hardwood edgebands as specified
Rails/Lock Blocks	Top Rail ³ / ₄ " "Firestop" minimum Bottom Rail 1 ³ / ₄ " "Firestop"
Core	Incombustible non-asbestos mineral core engineered to meet labeling requirements
Adhesives	Type 2. Type 1 available.
Faces	All commercially available hardwood species, medium density overlay, and high -pressure plastic laminates
Vision Panels & Louvers	See W.H.I. specifications
Prefitting	May be prefit to net sizes as specified
Machining	May be factory machined for hardware as specified
Warranty	Up to life of the original installation. See full Haley Brothers Warranty for specific coverages
Short Form Specification	Doors shall be "45 or 60 Minute Label," manufactured according to the specifications shown in the Haley catalog

NOTE: All dimensions are before trimming. "Firestop" is a product of Georgia-Pacific Corporation.