2-PANEL BELL TOP TEXTURED

Bold, sleek, stylish, this interior door brings chic to any room.

6'8" Sizes Available

1'0"	1"2"	1'3"	1'4"	1'6"	1'8"	1'10"	2'0"	2'2"	2'4"	2'6"	2'8"	2'10"	3'0"
			■	■	■		■	■	■	■	■	■	■

Durable, Long Lasting Performance

Made from molded high-density fiberboard, Haley Bros 2-panel bell-top resists shrinking, swelling cracking and joint separation. Engineered wood designs out performs wood doors while offering *superior value.* Available in standard 6'8' passage sizes with oak wood grain texture finish.

Haley offers a limited 1-year warranty for quality and craftsmanship on all residential molded panel doors.

HALEY

- Available in 6´8″ passage sizes.

- Most sizes can be specified for either hollow or solid core construction and with either finger joint or MDF stiles and rails.

- Oak wood grain texture finish.

- Available in 20, 45 and 60-minute fire ratings.

- All doors are available primed with a low VOC primer; ready to paint.

- Covered by a 1-year limited warranty for interior use.

GREEN BENEFITS

Haley molded door designs (facings) meet Phase 2 of the California Air Resources Board (CARB) Airborne Toxic Control Measure (ATCM) 93120.

Haley molded door designs contain No Added Urea Formaldehyde (NAUF.)

All hollow core Haley interior passage content doors contain a minimum of 25% pre-consumer recycled wood fiber content.

HALEY BROS., INC.
6291 Orangethrorpe Ave
Buena Park, CA 90620

Ph: 800-854-5951
info@haleybros.com
www.haleybros.com

HALEY

MOLDED DOOR-
DIMENSIONAL SPECIFICATIONS

2-Panel Bell Top

Bead and Cove Profile

2-Panel Bell Top

MOLDED DOOR DESIGN (DOOR FACING) SIZE

Overall length and width dimensions +/- 1/16"

Nominal	A	B	C	D
36	36.375	5.69	25.00	- -
34	34.375	5.77	22.84	- -
32	32.375	4.77	22.84	- -
30	30.375	5.35	19.69	- -
28	28.375	5.13	18.11	- -
26	26.375	5.71	14.96	- -
24	24.375	4.71	14.96	- -
20	20.375	5.44	9.50	- -
18	18.375	4.44	9.50	- -
16 U	16.375	4.69	7.00	- -
18/18 B	36.375	6.19	9.50	5.00
16/16 B	32.375	4.78	9.50	3.81
15/15 B	30.375	4.61	8.68	3.81
14/14 B	28.375	4.34	7.94	3.81
12/12 B	24.375	3.49	6.79	3.81