



# JAMB MACHINING SPECIFICATIONS

CORP. OFFICE 6291 ORANGETHORPE AVE., BUENA PARK, CA 90620  
PHONE (714) 670-2112 FAX (714) 994-6971

SPEC#

## HINGES

← BOTTOM OF DADO

### HINGES

SIZE

THICKNESS

BACKSET

### CORNERS

1/4 RADIUS

5/8 RADIUS

SQUARE

Fullbound

## LATCH

### STRIKES

2 1/4 FULL LIP (STD)

2 3/4 " T "

4 7/8 ASA

OTHER

### CORNERS

1/4 RADIUS

SQUARE

Diagram illustrating the JAMB MACHINING SPECIFICATIONS. The diagram shows a vertical cross-section of a door jamb with various dimensions and specifications marked. The left side is labeled 'HINGES' and the right side is labeled 'LATCH'. The diagram includes dimensions for the bottom of the dado, hinge size, thickness, backset, corners (1/4 radius, 5/8 radius, square), and fullbound. The latch side includes dimensions for the strike (2 1/4 full lip (std), 2 3/4 " T ", 4 7/8 ASA, other), corners (1/4 radius, square), and the net jamb height from the dado.

CUSTOMER NAME

SPEC. COMPLETED BY

HALEY WORK ORDER #

SPEC. VERIFIED BY

DUE DATE

DOORS ON HALEY SI #