

# AUTOMATIC DOOR BOTTOM

## MORTISE

All Products on This Page:



- Fits Wood Fire Door Mortise Restrictions
- Use With a Threshold for Maximum Sealing Capability
- Specify Exact Net Length Required to Avoid Field Sizing
- Furnished  $\frac{1}{2}$ " Shorter Than Ordered to Fit Within Net Door Size (i.e. 36" is Furnished 35  $\frac{1}{2}$ ")
- ADB's from 12" to 18" Can be Cut Down  $\frac{1}{2}$ ". ADB's 20" and Over Can be Cut Down up to  $1\frac{1}{2}$ "
- Minimum Length  $11\frac{1}{2}$ ", Maximum Length 60"
- $\frac{3}{4}$ " Max Drop
- Black Plastic End Caps Furnished Standard
- BHMA Certified to ANSI/BHMA A156.22, 1,000,000 Cycle Test-Grade 1
- Lead Insert Available for Radiation Shield – Specify 'Lead Lined'

### 225SA

Clear Anodized Aluminum Mortise Automatic Door Bottom with Neoprene Seal



#### 225SA


Silicone

Mortise Required

$\frac{5}{8}$ " x  $1\frac{1}{2}$ "



$1\frac{1}{2}$ "



Neoprene,  
Silicone &  
Nylon Brush  
are Black